

# CANOPY

The Professional Choice

## Brush-On WOOD STAIN

- Deep penetration
- UV sunscreen
- Water repellent



Ideal for gazebo, wooden bridge, door and frame, shingles, deck, outdoor furniture, plywood and home siding.

## Why let rain, sun or insect destroy your home?

Sun bakes wood and drained off moisture. Mold and algae are unsightly. Rots breaks down wood structure integrity and looks ugly. Insect causes damages.

**CANOPY Brush On**, a premium quality, deep penetrating non-drying oil based sealer, contains ultra-violet additives and special oils formulated for long lasting and beautiful natural colours.

**CANOPY Brush On** is resistant to UV rays, protects against insects and discolouration.



### Features

- Different from polyurethane varnishes which form thick surfaces that cracks and loosen. They also look artificial
- **CANOPY Brush On** penetrates deep into the wood and not on the wood surfaces. The finishes penetrate into the wood pores where it solidifies and harden the wood surfaces from within. It allows wood to breathe when moisture is trapped, hence eliminating cracking, peeling and blistering
- Removal of previous finishes is not necessary making re-coating easy
- Scratches and blemishes are easily repaired on the spot.
- This is easy compare to varnish.



### Surface Preparation & Application

Ensure that surface is thoroughly dry, **CANOPY Brush On** will not penetrate fully on wet or damp surfaces. Surfaces should be free of wax, oil or contaminates which may inhibit absorption and penetration. Two coats are normally recommended. However for extra protection you may apply three coats. After each coat allow 4 to 6 hours to dry, or overnight. Before second coat, sanding with 320 grit sanding paper is required. The coating should be touch dried in 2 hours.



### 4 way Protection

- Protection against UV, prevents wood from cracking, splitting, fading and discoloration.
- Protection against water
- Mild protection against mould, sap-stain and decay fungi
- Mild protection against insect



### Packaging

Available in 1 quart (0.946L), 1 gallon (3.785 L), 5 gallon (18.93 L).



### Coverage

400 to 600 sq feet per gallon for smooth surfaces



### Cleaning

Use white spirit or thinner



Contain petroleum distillates.  
Keep out of reach of children  
Use in well ventilated areas

---

**Arch Wood Protection (M) Sdn. Bhd.** (15229-X)  
No.1-1 Jalan 109E, Desa Business Park,  
Taman Desa, 58100 Kuala Lumpur.  
Tel : 03 79814002 Fax: 03 79815886  
[www.tanalised.com](http://www.tanalised.com)

